



TEXAS SUPER OUTBOARD TC-W3

High Performance 2-Stroke Outboard Motor Oil

PRODUCT DATA SHEET

Issue on 17 August 2017

Texas Petrochemical Asia Pacific Pte Ltd

Singapore 629170

Tel: 65-6262 6538

Fax: 65-6262 6537

Website: www.texaslub.com

DESCRIPTION

TEXAS SUPER OUTBOARD MOTOR OIL is a high performance two stroke marine outboard engine oil for use in 2T water-cooled outboard engines operating at all fuel to oil ratio specified by the OEMs. It incorporates a low ash additive treatment to ensure minimum deposits and to reduce spark plug fouling.

It is suitable for two strokes engines where the manufacturers call for NMMA TC-W3 engine oil.

PERFORMANCE STANDARDS

- Exceeds TC-W3 requirement

MAIN APPLICATION

Recommended for use in all air or water cooled two stroke outboard engines (both pre-mix and direct oil injection) at manufacturers recommended mixed ratios where appropriate.

BENEFITS

- Anti-wear properties for engine protection
- Low minimum deposits and reduced spark plug fouling
- Corrosion protection

TYPICAL PROPERTIES

TCW-3

Density, kg/Litre @ 15°C	0.8640
Kinematic Viscosity, mm ² /s @ 40°C	52.75
Kinematic Viscosity, mm ² /s @ 100°C	8.55
Viscosity Index	120
Sulphated Ash, wt%	0.001
Pour Point, °C	-40
Flash Point COC, °C	98
TBN	5.5

Typical physical and chemical characteristics do not constitute as specifications. Texas Petrochemical reserves the right to amend and change the information herein without notification as a result of continual product research and development.