

PRODUCT DATA SHEET

Issue on 14 April 2017
Texas Petrochemical Asia Pacific Pte Ltd

Singapore 629170 Tel: 65-6262 6538 Fax: 65-6262 6537 Website: <u>www.texaslub.com</u>

TEXAS TEXMARINE LS 200 TBN 20 SAE 50

Superior Quality Cylinder Lubricant

DESCRIPTION

TEXAS TEXMARINE LS 200 is alkaline marine diesel engine cylinder lubrication suitable for low speed twostroke diesel engines and running on low Sulphur distillate fuels and all ultra-low Sulphur fuel oils.

PERFORMANCE STANDARDS

API CF

MAIN APPLICATION

 Cylinder Lubrication of low and Ultra-Low Sulphur distillate fuels and ultra-low Sulphur fuel oils with Sulphur Content < 0.10% specifically for vessels operating in Emission Control Areas (ECA).

BENEFITS

- High level of dispersion and detergency
- Excellent resistance to oxidation at high temperatures
- High load carrying capacity
- Excellent anti-wear, anti-rust and anti- foaming properties

TYPICAL PROPERTIES

TEXMARINE LS 200	SAE 50
Density, kg/Litre @ 15°C	0.905
Kinematic Viscosity, mm ² /s @ 40°C	223.9
Kinematic Viscosity, mm ² /s @ 100°C	19.0
Viscosity Index	100
Pour Point, °C	-12
Flash Point COC, °C	230
TBN	20