



TEXAS TEXFRIGE AS SERIES

Synthetic Refrigerator Compressor Oil

PRODUCT DATA SHEET

Issued on 15th April 2016

Texas Petrochemical Asia Pacific Pte Ltd

80 International Road

Singapore 629170

Tel: 65-6262 6538

Fax: 65-6262 6537

Website: www.texaslub.com

DESCRIPTION

Texas Texfrige AS series Compressor Oils are superior quality synthetic refrigeration lubricants with a polyolester base fluid. It is developed for use with R 134a and other HFC refrigerants.

BENEFITS

- Extended maintenance Intervals
- Wear Protection
- Refrigerant Compatibility with R 134a and other HFC refrigerants
- Seal Compatibility

TYPICAL APPLICATIONS

- Developed for use with R134a and other HFC refrigerants
- Can be used in open, semi-open and hermetic compressors in domestic, commercial and industrial refrigeration systems.
- Can be used in rotary and reciprocating compressors.
- Compatible with all sealing materials commonly used with fluorocarbon refrigerant systems.

Performance Standards

- DIN 51503 KD

TYPICAL PROPERTIES

ISO Grade	R32	R46	R68
Density, kg/liter @ 15°C	0.98	0.97	0.96
Kinematic Viscosity, mm ² /s @ 40°C	30.4	45.1	66.9
Pour Point, °C	-55	-55	-45
Flash Point COC, °C	195	200	210